

1. PERFORMANCE


- 1) Measuring range : 10-500 ppm
- Number of pump strokes : 1 (100mℓ)
- 2) Sampling time : 1.5 minutes/1 pump stroke
- 3) Detectable limit : 1 ppm
- 4) Shelf life : 1 year (Necessary to store in a refrigerated place ; 0 ~ 10 °C)
- 5) Operating temperature : 0 ~ 40 °C
- 6) Temperature compensation : Necessary (See "TEMPERATURE CORRECTION TABLE")
- 7) Reading : Direct reading from the scale calibrated by 1 pump stroke
- 8) Colour change : White → Orange

2. RELATIVE STANDARD DEVIATION

RSD-low : 15 % RSD-mid. : 15 % RSD-high : 10 %

3. CHEMICAL REACTION

By decomposing with an Oxidizer, chlorine is produced. Yellowish Orthoquinone is produced by reacting between this Chlorine and *o*-Toulidine.





4. CALIBRATION OF THE TUBE

GAS CHROMATOGRAPHY

5. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	Coexistence
Alcohols	The accuracy of readings is not affected.	The accuracy of readings is not affected.
Esters	∕	∕
Aromatic hydrocarbons	∕	∕
Aliphatic hydrocarbons FIG.1	∕	∕
Halogenated hydrocarbons FIG.2	Similar stain is produced.	Higher readings are given.



TEMPERATURE CORRECTION TABLE

Scale Readings (ppm)	True Concentration (ppm)				
	0 °C (32 °F)	10 °C (50 °F)	20 °C (68 °F)	30 °C (86 °F)	40 °C (104 °F)
500	—	685	500	415	350
400	—	550	400	330	275
300	—	400	300	240	200
200	380	265	200	165	130
100	175	130	100	75	60
50	90	70	50	40	37
30	55	40	30	20	15
10	20	14	10	7	5